



Bowers & Wilkins

702 S3 Signature

Technical Information



Technical Features

Decoupled Carbon Dome tweeter
Solid Body Tweeter-on-Top
Continuum™ cone FST™ midrange
Decoupled midrange
Aerofoil™ Profile bass cones
Flowport™

Description

3-way vented-box system

Drive Units

1x ø25mm (1 in) Decoupled Carbon Dome high-frequency
1x ø150mm (6 in) Continuum cone FST midrange
3x ø165mm (6.5 in) Aerofoil Profile bass

Frequency Range

-6dB 28Hz - 33kHz

Frequency Response (+/-3dB from reference axis)

46Hz - 28kHz ±3dB

Sensitivity (on axis at 2.83Vrms at 1m)

90dB

Harmonic Distortion

2nd and 3rd harmonics (90dB, 1m on axis)
<1% 86Hz - 28kHz
<0.5% 110Hz - 20kHz

Nominal Impedance

8Ω (minimum 3.1Ω)

Recommended Amplifier Power

30W - 300W into 8Ω on unclipped programme

Max. Recommended Cable Impedance

0.1Ω

Dimensions

Height: 1,010 mm (39.8 in) cabinet only
1,138 mm (44.8 in) including tweeter and plinth
Width: 192 mm (7.6 in) cabinet only
290 mm (11.4 in) including plinth
Depth: 354 mm (13.9 in) cabinet only
410 mm (16.1 in) including plinth
391 mm (15.4 in) including grille and terminals

Net Weight

35.26 kg (77.7 lbs)

Finishes

Cabinet: Datuk Gloss
Midnight Blue Metallic
Grille: Black