


## Pure and Simple

Wrapped in an exquisitely veneered cabinet, the 10 inch dual voice coil paper/Kevlar® driver is driven and controlled by the mega efficient 500W audiophile standard Class D amplifier and switch mode power supply, delivering immense power when the signal demands.



## Technical Specifications

<b>Description</b>	Active closed-box subwoofer system
<b>Drive units</b>	ø250mm (10 in) paper/Kevlar® cone long-throw driver ø76mm (3 in) dia voice coil - dual suspension diecast chassis
<b>Frequency range</b>	-6dB at 18Hz and 25/140Hz adjustable (EQ at A)
<b>Frequency response</b>	±3dB 25Hz – 40/140Hz adjustable (EQ at A)
<b>Bass Extension</b>	-6dB at 18Hz (position A) -6dB at 23Hz (position B) -6dB at 28Hz (position C)
<b>Amplifier Power output:</b>	Amplifier Power output: 500W Rated power consumption: 94W Standby: 0.8W Idle (ON no signal) 11.8W Input impedance: 33kΩ Signal / noise: >80dB
<b>Functions:</b>	Input level (line in) Input level (speaker in) Low-pass filter frequency Low-pass filter bypass (line in only) Bass extension Bass roll-off alignment Auto sense on/standby Phase switch
<b>Inputs:</b>	Line In (RCA Phono) Speaker in (Binding post) 12v trigger (3.5mm jack)
<b>Low-pass filter</b>	Active 4th-order, variable cut-off frequency
<b>Dimensions</b>	Height: 325 mm (12.8 in) not including feet Width: 325 mm (12.8 in) Depth: 362mm (14.3 in) including grille and controls
<b>Net weight</b>	19.5kg (43 lb)
<b>Finish</b>	Cabinet: Gloss Black Grille: Black



Gloss black