



Pure and Simple

Wrapped in an exquisitely lacquered cabinet, the 12 inch dual voice coil paper/Kevlar® driver is driven and controlled by the mega efficient 500W audiophile standard Class D amplifier and switch mode power supply, delivering immense power when the signal demands.

Technical Specifications

Description	Active closed-box subwoofer system
Drive units	ø300mm (12 in) paper/Kevlar® cone long-throw driver ø76mm (3 in) dia voice coil - dual suspension diecast chassis
Frequency range	-6dB at 18Hz and 25/140Hz adjustable (EQ at A)
Frequency response	±3dB 25Hz – 40/140Hz adjustable (EQ at A)
Bass Extension	-6dB at 18Hz (position A) -6dB at 23Hz (position B) -6dB at 28Hz (position C)
Amplifier Power output:	Amplifier Power output: 500W Rated power consumption: 94W Standby: 0.8W Idle (ON no signal) 11.8W Input impedance: 33kΩ Signal / noise: >80dB
Functions:	Input level (line in) Input level (speaker in) Low-pass filter frequency Low-pass filter bypass (line in only) Bass extension Bass roll-off alignment Auto sense on/standby Phase switch
Inputs:	Line In (RCA Phono) Speaker in (Binding post) 12v trigger (3.5mm jack)
Low-pass filter	Active 4th-order, variable cut-off frequency
Dimensions	Height: 395 mm (15.5 in) not including feet Width: 395 mm (15.5 in) Depth: 432mm (17.0 in) including grille and controls
Net weight	24.5kg (54 lb)
Finish	Cabinet: Gloss Black Grille: Black